



ARM Caster HD

Micro-Sized Digital Signage Player Powered by Raspberry Pi 3



Features

- ✓ Quiet operation
- ✓ GPU – Broadcom VideoCore IV
- ✓ Linux/ARM
- ✓ 10/100 Ethernet Port for Internet Access
- ✓ 4 x USB ports

Ordering Information

ARM Caster HD: 1.2GHz 64-bit quad-core ARM Cortex-A53

ARM Caster HD Guidelines:

- No more than one video section can run at a time.
- The max number of recommended zones on a layout are (3) three.
- Videos have to be in MP4 format with H.264
- No more than two Flash zones can play at the same time.

Standard Color	Black
CPU	1.2GHz 64-bit quad-core ARM Cortex-A53 CPU
Construction	Acrylic
OS	Linux / ARM
RAM	1GB
Video Out:	1 x HDMI
Network	10/100 Ethernet, 2.4GHz, 802.11n wireless and Bluetooth 4.1
Temperature:	Operating : 10 ~ 35 °C Storage : -10 ~ 48 °C
Size:	4" x 2.75" x 1"
Weight	0.2lbs
SoC	Broadcom BCM2837
Ports	3.5mm audio-video jack 4 x USB 2.0, Ethernet port

* All specifications and photos are subject to change without notice.