





## SignEdge Pro Series

Embedded Standalone Digital signage Player with Built in CMS

SignEdge Dico	
Construction CPU	Aluminum die-casting Integrated Dual-core Intel® Atom <sup>™</sup> processor D525 1.8GHz
System Memory	2GB pin DDRII max. up to 4GB
Graphic Chipset	
Video Out:	1 x HDMI connector 1 x DVI connector /VGA
Network	1 Realtek® RTL8111D Gigabit LAN controller 1 Wireless 802.11N
Storage:	250 GB HD
Audio:	ALC662 High Definition Audio CODEC Supports Optical S/PDIF out ports on rear Blu-ray support
Power Supply:	150W DC Adapter (19V, 4.74A)
Temperature:	Operating : 10 ~ 35 °C Storage : -10 ~ 48 °C
Size:	190(w)x190(D)x35(H)mm; 7.5(W)x7.5(D)x1.4(H)"
OS:	Linux

### **Features**

- Quiet operation
- Dual Monitor Functionality
- High Resolution 1920x1080
- Onboard Intel® dual Core processor
- High performance with extremely low power
- Full feature I/O
- Flexible Block for customization
- 250GB Hard Drive
- Watchdog Timer
- 80 Watt AC-in or 70 Watt DC-in power supply
- Wireless 802.11N, LAN,

### **Ordering Information**

Standard	
SignEdge pro	With Intel® Dual Core Atom 1.8Ghz
SignEdge Extreme	With Intel® i5
Option	
	Option
SignEdge TV	Option Live TV Input
SignEdge TV	



#### M1 wall mounting bracket

- Wall mount bracket
- Set of two brackets
- M3 Screws Included
- Wall screws not included.



\* All specifications and photos are subject to change without notice.





# SignEdge Pro Web interface

Embedded Standalone Digital signage Player with Built in CMS

